

# DILUENTE NA23

Thinner

## NATURE AND USE

Thinner for the spray application of all nitrocellulose based products, primers and rust preventers (fast drying), for spray application or dipping.  
Use in the suggested percentage stated in the TDS of the product.

## TECHNICAL DATA

**Specific gravity:** Kg/l 0,867 @ +20°C  
**Colour:** Colourless



## APPLICATION DETAILS

**Use:** Thinner suitable for all nitrocellulose fast drying products.  
**Thinning:** % Keep the percentage suggested in the Technical Data Sheet of the product to thin.  
**Cleaning:** Suitable for the cleaning of equipment used for the application of involved products.

## HANDLING STORAGE AND SAFETY PRECAUTIONS

**Warning:** All handling and/or use activities of the product must strictly refer to the given indications in the Safety Data Sheet. The following advices are suggested by the common sense and in good faith, they are uncompleted and do not substitute the content of the specific safety data sheet of the product.

**Handling:** The material must be used only by professional and qualified applicators suitably trained. All the operations involving the use of the product, must be carried on in compliance with all the relevant National Health, Safety & Environmental Standards and Regulations.

**Precautions:** When the product is used inside enclosed areas ( i.e rooms, containers, vessels) it is imperative to provide the necessary air circulation using adequate means and must be granted during the whole time required by application and coating polymerization, to avoid conditions open to potential explosion danger.

All electrical installations must always be grounded. Where explosion hazards exist, the workmen should be required to use only non-ferrous tools and wear conductive non-sparking shoes and clothing. Explosion and flame-proof equipment too are imperative.

**Storage and transport:** Keep far from flames, sparks or heat sources. Do not leave exposed under the direct solar action. Store under shelter in original unopened packaging, in cool, dry and ventilated areas at ambient temperatures between +5°C and +35°C.

**Shelf life:** 36 months in the suggested storage conditions (original unopened packaging)

N.B.: Product for professional use only  
and exclusively for the uses not regulated under CE Directive 2004/42/CE.

Refer to Material Safety Data Sheet

MTDS 01018/ Page 1 of 1

The content of the present technical data sheet is the most complete currently available, based on practical experience and given in good faith. Should any change be necessary, the present data sheet will be updated without prior notice. The applying conditions of use differ according to environmental conditions and subjective application factors outside the control of the Company. The user shall determine the suitability of the product for the intended use under his own risk and responsibility. No warranty is impressed or implied. The Company refuses all liability not directly related with defects of the product or consequent to deviations from written instructions.



INDUSTRIE BRUNO STOPPANI R.P.S. S.r.l.

Sede Operativa: Via Industriale 90-119 25020 Capriano del Colle (Bs) – Italy - Phone +39 030 9745116 – Fax +39 030 9745383

sales@industri brunostoppa nipa nts.com - [www.industrie brunostoppa nipa nts.com](http://www.industrie brunostoppa nipa nts.com)

Company with quality management system UNI EN ISO 9001:2015 certified