

NATURE AND USE

Stoppiù is a washable water-based wall paint for interiors and exteriors, characterised by excellent coverage and spreading rate, excellent whiteness and exceptional resistance to washability. Top of the range of the Stoppani Industrial building line, Stoppiù is a paint formulated with styrene-acrylic resins in emulsion, inorganic and organic pigments resistant to light and selected inert mineral extenders. The product has a high resistance to washability tested in accordance with ASTM D 2486 (over 30,000 double brush strokes) and is easily applicable with traditional systems on masonry walls, wooden substrates, etc., duly primed. Just two coats of product allow you to obtain a uniform finish. **Paint meeting ECO LABEL product requirements.** **Ecolabel for interior paints – Innovhub SSI test report Nro S-ISSI-2305515**

TECHNICAL DATA



Type of Binder:	Styrene – Acrylic
Appearance:	Thixotropic
Specific weight:	Kg/l 1,45 ± 0,100 @ +20°C
Solids by weight:	% 56 ± 2%
Colour:	White and on request

SUBSTRATE PREPARATION

New plaster: The substrate must be perfectly cured, dry, clean and brushed; completely free from easily detachable friable particles. Then proceed to apply a coat of primer to even out the absorption of the substrate using a special Insulating fixative, then apply 2 coats of Stoppiù.

Already painted plaster: Old paints that are not perfectly anchored must be removed mechanically. Then proceed as on a new substrate.

APPLICATION DETAILS

Application:	Brush, roller, spray
Thinner:	Water
Thinning:	% 20 – 40
Pulizia attrezzi:	Water
Drying @ +25°C:	3-6 hours
Overcoating @ +20°C:	8 -16 hours (R.H. equal to 50%) N.B.: Minimum temperature for film forming is +5°C
Application Temperature:	°C Between +5°C e +40°C
Relative Humidity:	% Not exceeding 80
Suggested Thickness:	40 - 45 µm dry (DFT) per coat (wet WFT about 125 µm)

MTDS 0424/ Page 1 of 3

The content of the present technical data sheet is the most complete currently available, based on practical experience and given in good faith. Should any change be necessary, the present data sheet will be updated without prior notice. The applying conditions of use differ according to environmental conditions and subjective application factors outside the control of the Company. The user shall determine the suitability of the product for the intended use under his own risk and responsibility. No warranty is impressed or implied. The Company refuses all liability not directly related with defects of the product or consequent to deviations from written instructions.



INDUSTRIE BRUNO STOPPANI R.P.S. S.r.l.

Sede Operativa: Via Industriale 90-119 25020 Capriano del Colle (Bs) – Italy - Phone +39 030 9745116 – Fax +39 030 9745383

sales@industri brunostoppa nipa nts.com - www.industri brunostoppa nipa nts.com

Azienda con sistema di gestione qualità UNI EN ISO 9001:2015 certificato

Theoretical spreading rate: m^2/l 8 / 9 per coat at the suggested thickness

More info by writing to sales@industri brunostoppa nipa ntpa nts.com or by calling +39 030 9745116

HANDLING
STORAGE AND
SAFETY
PRECAUTIONS

Warning: All handling and/or use activities of the material and its components must strictly refer to the given indications in the Safety Data Sheet. The following advices are stated by common sense and in good faith, they are uncompleted and do not substitute the content of each specific safety data sheet of the product.

Handling: The material must be used only by professional and qualified applicators suitably trained. All the operations involving the use of the product, must be carried on in compliance with all the relevant National Health, Safety & Environmental standards and regulations.

Precautions: When the product is used in enclosed areas (rooms, containers, vessels, etc.) it is imperative to use adequate means providing the necessary air circulation, to be granted during the whole application and coating polymerization time, also to avoid conditions open to potential explosion danger.

All electrical installations must always be grounded. Where explosion hazards exist, the workmen should be required to use only non-ferrous tools and wear conductive non-sparking shoes and clothing. Explosion and flame-proof equipment too are required.

Storage and transport: Keep far from flames, sparks or heat sources. Do not leave exposed under direct solar action. Store under shelter in original unopened packaging, in cool, dry and ventilated areas, at temperatures between +5°C and +35°C.

Shelf life: 12 months in the suggested storage conditions (original unopened packaging)

N.B.: **Product for professional use only**
and exclusively for the uses not regulated under CE Directive 2004/42/CE.

Refer to Material Safety Data Sheet



Access catalogues, data sheets and company presentations

MTDS 0424/ Page 2 of 3

The content of the present technical data sheet is the most complete currently available, based on practical experience and given in good faith. Should any change be necessary, the present data sheet will be updated without prior notice. The applying conditions of use differ according to environmental conditions and subjective application factors outside the control of the Company. The user shall determine the suitability of the product for the intended use under his own risk and responsibility. No warranty is impressed or implied. The Company refuses all liability not directly related with defects of the product or consequent to deviations from written instructions.



INDUSTRIE BRUNO STOPPANI R.P.S. S.r.l.

Sede Operativa: Via Industriale 90-119 25020 Capriano del Colle (Bs) – Italy - Phone +39 030 9745116 – Fax +39 030 9745383

sales@industri brunostoppa nipa ntpa nts.com - www.industri brunostoppa nipa ntpa nts.com

Azienda con sistema di gestione qualità UNI EN ISO 9001:2015 certificato



Washable water-based paint for interiors and exteriors

MTDS 0424/ Page 3 of 3

The content of the present technical data sheet is the most complete currently available, based on practical experience and given in good faith. Should any change be necessary, the present data sheet will be updated without prior notice. The applying conditions of use differ according to environmental conditions and subjective application factors outside the control of the Company. The user shall determine the suitability of the product for the intended use under his own risk and responsibility. No warranty is impressed or implied. The Company refuses all liability not directly related with defects of the product or consequent to deviations from written instructions.



INDUSTRIE BRUNO STOPPANI R.P.S. S.r.l.

Sede Operativa: Via Industriale 90-119 25020 Capriano del Colle (Bs) – Italy - Phone +39 030 9745116 – Fax +39 030 9745383

sales@industri brunostoppa nipa nts.com - www.industri brunostoppa nipa nts.com

Azienda con sistema di gestione qualità UNI EN ISO 9001:2015 certificato